Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 8 (replaces version 7) Revision: 16.06.2023

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Aqua PF- 430 Pigment Filler [iac]

Article number: 3265, 3267, 3269

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.
Product category PC9b Fillers, putties, plasters, modelling clay
Application of the substance / the mixture Filler and surfacer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH
Bernhard-Remmers-Str. 13
D-49624 Löningen / Germany
Tel.: +49(0)5432/83-0
Fax: +49(0)5432/3985

Remmers (UK) Limited
Unit 4 , Lloyds Court
Manor Royal, Crawley – West Sussex RH10 9QU
fon +44 (0) 1293 594 010
fax +44 (0) 1293 594 037

Information department:
Product Safety department: Phone: +44 (0) 1293 594 010
Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS):
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:
within USA and Canada: 1-800-424-9300
outside USA and Canada: 001-703-527-3887

*

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008
The product is not classified, according to the GB CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void
Hazard pictograms Void
Signal word Void
Hazard statements Void
Additional information:
EUH208 Contains adipic acid dihydrazide, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3 Other hazards

Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

*

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: aqueous dispersion

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 8 (replaces version 7) Revision: 16.06.2023

Trade name Aqua PF- 430 Pigment Filler [iac]

(Contd. of page 1)

Dangerous components [% w/w]:		
CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35-XXXX	barium sulphate, natural substance with a Community workplace exposure limit	≥10-<20%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide substance with a Community workplace exposure limit	≥10-<20%
CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0	2-butoxyethanol Acute Tox. 3, H331; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg LC50/4 h inhalative: 3 mg/l	≥2.5-<5%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-XXXX	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	≥0.5-≤1%
CAS: 1071-93-8 EINECS: 213-999-5	adipic acid dihydrazide Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥0.5-<1%
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6	1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317:C ≥ 0.05 %	≥0.0015-<0.05%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
After inhalation No special requirements.
After skin contact If skin irritation continues, consult a doctor.
After eye contact Rinse opened eye for several minutes under running water.
After swallowing Seek immediate medical advice.
4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents Use fire fighting measures that suit the environment.
5.2 Special hazards arising from the substance or mixture No further relevant information available.
5.3 Advice for firefighters
Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation
6.2 Environmental precautions:
Do not allow to enter the ground/soil.
Dilute with plenty of water.
6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
6.4 Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 8 (replaces version 7) Revision: 16.06.2023

Trade name Aqua PF- 430 Pigment Filler [iac]

(Contd. of page 2)

SECTION 7: Handling and storage

7.1 Precautions for safe handling
No special measures required.
No special precautions necessary if used correctly.

7.2 Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and containers: No special requirements.
Information on storage in a common storage facility: none
Further information about storage conditions:
Protect from frost.
Store cool.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:	
CAS: 7727-43-7 barium sulphate, natural	
WEL	Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust
CAS: 13463-67-7 titanium dioxide	
WEL	Long-term value: 10* 4** mg/m³ *total inhalable **respirable
CAS: 111-76-2 2-butoxyethanol	
WEL	Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV
CAS: 34590-94-8 (2-methoxymethylethoxy)propanol	
WEL	Long-term value: 308 mg/m³, 50 ppm Sk

Ingredients with biological limit values:	
CAS: 111-76-2 2-butoxyethanol	
BMGV	240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls
Appropriate engineering controls No further data; see item 7.
Individual protection measures, such as personal protective equipment
General protective and hygienic measures
Do not eat, drink or smoke while working.
Use skin protection cream for preventive skin protection.
Avoid close or long term contact with the skin.
Wash hands before pauses and after work.
The following indication regarding the personal protective equipment are to be considered as suggestions.The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances.If a risk assessment on-site shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.
Respiratory equipment:
Respiratory protection if there is a risk of splashes/mist.
Filter A/P2.
Hand protection
Protective gloves or protective skin cream.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 8 (replaces version 7) Revision: 16.06.2023

Trade name Aqua PF- 430 Pigment Filler [iac]

(Contd. of page 3)

Material of gloves
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Penetration time of glove material
The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
Eye/face protection if there is a risk of splashes
Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties	
General Information	
Physical state	Fluid
Colour:	White
Odour:	Solvent-like
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	100 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	>100 °C
Ignition temperature:	not applicable
Decomposition temperature:	Not determined.
pH at 20 °C	8.2
Viscosity:	
Kinematic viscosity at 20 °C	ca. 28 s (ISO 6 mm)
dynamic:	Not determined.
Solubility	
Water:	Fully miscible
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	ca. 1.45 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Explosive properties:	Product is not explosive.
Solvent separation test	< 3 %
VOC EU	<130 g/l
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 8 (replaces version 7) Revision: 16.06.2023

Trade name Aqua PF- 430 Pigment Filler [iac]

(Contd. of page 4)

Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.
10.2 Chemical stability
Thermal decomposition / conditions to be avoided:
No decomposition if handled and stored according to specifications.
10.3 Possibility of hazardous reactions No dangerous reactions known
10.4 Conditions to avoid No further relevant information available.
10.5 Incompatible materials: No further relevant information available.
10.6 Hazardous decomposition products: No dangerous decomposition products known

*
SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:		
CAS: 111-76-2 2-butoxyethanol		
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	mg/kg (rabbit)
Inhalative	LC50/4 h	3 mg/l (ATE)

Skin corrosion/irritation: Based on available data, the classification criteria are not met.
Serious eye damage/irritation: Based on available data, the classification criteria are not met.
Sensitisation: Based on available data, the classification criteria are not met.
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.
STOT-single exposure: Based on available data, the classification criteria are not met.
STOT-repeated exposure: Based on available data, the classification criteria are not met.
Aspiration hazard: Based on available data, the classification criteria are not met.
11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

*
SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity: No further relevant information available.
12.2 Persistence and degradability No further relevant information available.
12.3 Bioaccumulative potential No further relevant information available.
12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 8 (replaces version 7) Revision: 16.06.2023

Trade name Aqua PF- 430 Pigment Filler [iac]

(Contd. of page 5)

12.5 Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.
12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
12.7 Other adverse effects
Additional ecological information:
General notes:
Do not allow product to reach ground water, bodies of water or sewage system.
Do not allow undiluted or larger quantities of the product to reach ground water, bodies fo water or sewage system.

SECTION 13: Disposal considerations

Recommendation
Liquid material remains are to be disposed of at collection facilities for old varnishes.
The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user´s, other codes may apply under other conditions.

European waste catalogue	
08 01 19*	aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances

Uncleaned packaging:
Recommendation:
Disposal must be made according to official regulations.
Packaging can be reused or recycled after cleaning.
Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

14.1 UN number or ID number **ADR, ADN, IMDG, IATA**	Void
14.2 UN proper shipping name **ADR, ADN, IMDG, IATA**	Void
14.3 Transport hazard class(es) **ADR, ADN, IMDG, IATA** **Class**	Void
14.4 Packing group **ADR, IMDG, IATA**	Void
14.5 Environmental hazards: **Marine pollutant:**	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	Not a hazardous good according to the above regulations.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU
Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.06.2023 Version number 8 (replaces version 7) Revision: 16.06.2023

Trade name Aqua PF- 430 Pigment Filler [iac]

(Contd. of page 6)

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS
None of the ingredients is listed.

National regulations

Other regulations, limitations and prohibition ordinances

Observe the usual protective measures when working and for storage.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.
Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS
Date of previous version: 18.07.2022
Version number of previous version: 7

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2